

SITOR fuse link, with blade contacts, NH2, In: 350 A, gS, Un AC: 690 V, Un DC: 250 V, front indicator



Figure similar

Model	
Product brand name	SETRON
Product designation	SITOR fuse link
Design of the product	With blade contacts
Design of an identification indicator	front indicator
Design of the switching contact	With blade contacts, silver-plated
Design of the fuse link	SITOR, LV HRC design

General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH2
Operating class of the fuse link	gS
Diken-export / Let-through current	DS_3NE_2_690_gS_500
circuit-breaker / Design	3NE
Varying load factor (WL)	1
Supply voltage	
• at AC / rated value	690 V
• at DC	250 V

Switching capacity

Switching capacity current	
<ul style="list-style-type: none"> • acc. to IEC 60947-2 / rated value 	100 kA

Dissipation

Power loss [W]	42 W
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	42 W

Electricity

Tripping residual / rated value / derated current / at 40 Cel	350 A
Current / at AC / rated value	350 A
Diken-export / Let-through energy	DE_3NE_2_690_gS_500

Product details

Product description	Not non-interchangeable
---------------------	-------------------------

Mechanical Design

Mounting position	Any, preferably vertical
-------------------	--------------------------

Environmental conditions

Ambient temperature	
<ul style="list-style-type: none"> • minimum • maximum 	-20 °C 50 °C
Environmental category	-20 to +50 at 95% relative humidity

Certificates

Reference code	
<ul style="list-style-type: none"> • acc. to DIN EN 61346-2 • acc. to DIN EN 81346-2 	F F

General Product Approval	Declaration of Conformity	other
---------------------------------	----------------------------------	--------------



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE1331-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NE1331-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE1331-0

CAX-Online-Generator

<http://www.siemens.com/cax>

