

Device Type	I <sub>O</sub> Rated Amps	V <sub>OUT</sub> Volts	V <sub>IN</sub> Volts Max	PD Watts Rated	V <sub>IN</sub> -V <sub>OUT</sub> Differential Volts Min	Regulator %V <sub>OUT</sub> T <sub>A</sub> = 25 °C		T <sub>J</sub> °C Max	T <sub>C</sub> % V <sub>O</sub> / °C	Outline Drawing
						Line	Load			

### POSITIVE HYBRID FIXED VOLTAGE

LAS-2105	5	5	40	85	4.6	0.1	0.2	200	0.015	J
LAS-2112	5	12	40	85	4.6	0.1	0.2	200	0.015	J
LAS-2115	5	15	40	85	4.6	0.1	0.2	200	0.015	J
LAS-2124	3	24	40	85	4.6	0.1	0.2	200	0.015	J
LAS-2205	5	5	40	85	2.5	0.1	0.2	200	0.015	K
LAS-2206	5	6	40	85	2.5	0.1	0.2	200	0.015	K
LAS-2212	5	12	40	85	2.5	0.1	0.2	200	0.015	K
LAS-2215	5	15	40	85	2.5	0.1	0.2	200	0.015	K
LAS-2224	3	24	40	85	2.5	0.1	0.2	200	0.015	K
LAS-3205	10	5	40	140	2.5	0.1	0.2	200	0.015	K
LAS-3212	8.5	12	40	140	2.5	0.1	0.2	200	0.015	K
LAS-3215	8.5	15	40	140	2.5	0.1	0.2	200	0.015	K
LAS-3224	7.5	24	40	140	2.5	0.1	0.2	200	0.015	K
LAS-3228	7.0	28	40	140	2.5	0.1	0.2	200	0.015	K
LAS-5205	20	5	40	270	2.5	0.14	0.2	200	0.015	L
LAS-5212	15	12	40	270	2.5	0.14	0.2	200	0.015	L
LAS-5215	15	15	40	270	2.5	0.14	0.2	200	0.015	L
LAS-5224	14	24	40	270	2.5	0.14	0.2	200	0.015	L
LAS-7205	30	5	40	400	2.5	0.14	0.2	200	0.015	M
LAS-7215	22	15	40	400	2.5	0.14	0.2	200	0.015	M
LAS-7224	21	24	40	400	2.5	0.14	0.2	200	0.015	M

Device Type	I <sub>O</sub> Rated Amps	V <sub>OUT</sub> Volts	V <sub>OUT</sub> Tolerance %	V <sub>IN</sub>		PD Watts Rated	REG (Line) %	REG (Load) %	T <sub>J</sub> °C Rated	T <sub>C</sub> % V <sub>O</sub> / °C	Outline Drawing
				Min	Max						

### NEGATIVE FIXED VOLTAGE

LAS-18A05	1.5	-5	±2	-7.1	-35	10	2.0	0.6	125	0.03	D
LAS-1805	1.5	-5	±5	-7.1	-35	10	2.0	0.6	125	0.03	D
LAS-18A12	1.5	-12	±2	-14.1	-35	10	2.0	0.6	125	0.03	D
LAS-1812	1.5	-12	±5	-14.1	-35	10	2.0	0.6	125	0.03	D
LAS-18A15	1.5	-15	±2	-17.1	-35	10	2.0	0.6	125	0.03	D
LAS-1815	1.5	-15	±5	-17.1	-35	10	2.0	0.6	125	0.03	D