

LMK Series



Model	LMK-2P	LMK-3P
Dimension(mm)	34.5×34.5×52.5	
Contact Form	2Z 2H 2D	3Z 3H 3D
Contact Material	Silver alloy	
Resistance Performance Of Contactor Capacity	10A/28VDC 10A/250VAC	
Coil Power at 23°C	DC(W)	≤1.5W
	AC(VA)	≤2.5VA
Coil Voltage	DC(V)	6~220V
	AC(V)	6~380V
Pick-up Voltage at 23°C	DC≤75% AC≤80%	
Drop-out Voltage at 23°C	DC≥10% AC≥30%	
Max Voltage at 23°C	110%	
Contact Resistance(at 6VDC 1A)	≤100mΩ	
Dielectric Strength	Between Open Contacts	≥1200VAC 50Hz/1min Leakage current 1mA
	Contacts pieces	≥1500VAC 50Hz/1min Leakage current 1mA
	Between Coil & Contacts	≥1500VAC 50Hz/1min Leakage current 1mA
Insulation Resistance(MΩ) at 500VDC	≥100MΩ	
Service life	Electrical	10 ⁵ Times(Frequency: On1Time/1S, Off1Time/1S)
	Mechanical	10 ⁶ Times(Frequency: 300Time/1min)
Ambient Temperature	-25°C~+55°C	
Terminal type	Insert type	
Suitable socket	LPF083A LPF083A-E LPL08	LPF113A LPF113A-E LPL11
Product Weight	76g	80g
Same Reference	JTX Universal	

LMK Installation dimensions and connecting diagram

